



LEADING THROUGH INNOVATION

FILTRATION

DIVERSIFIED SUPPLIES FOR THE FILTRATION INDUSTRY



Fil-Tec offers a wide variety of products for the filter bag industry. We offer a complete line of thread and bobbins, cuff beading and door seal gaskets. We service both domestic and international markets.

For more information about our product line, visit our website at www.fil-tec.com

DIVERSIFIED SUPPLIES FOR THE FILTRATION INDUSTRY

PRODUCT	SIZE / STYLE	FEATURES & BENEFITS
Sewing Thread:		
PTFE Coated Fiberglass	E-12 (Denier: 1395) E-18 (Denier: 2075) E-24 (Denier: 2800)	Will not burn 400° to 1000° F. Unaffected when exposed to most acids, alkali and solvents. High tensile strength.
Pro Polypropylene	69 & 92 (white)	Lubricated to provide consistent sewing performance. Low melt point (330° F) permits ease of recycling.
Bonded Polyphenylene	92 (natural)	Melt Point 545° F. Limited oxygen index of 35. Non-flammable. Chlorine bleach, chemical, sunlight, and acid resistant.
Premofast Bonded Polyester threads & bobbins	69 & 92 (white & yellow)	Continuous filament bonded thread which provides good resistance to acids. Available in 1 lb & 2 lb spools.
Bondex Bonded Nomex threads & bobbins	69 (Olive)	Will not melt or decompose up to 700° F. Resistant to bacteria and organic solvents.
PremoXT Bonded Nylon threads & bobbins	46,69, 92,138	Excellent sewability with superior UV resistance.
PremoLast PTFE thread	1800 denier	100% PTFE sewing thread which will withstand up to 550° F with good resistance to most chemicals.
Dust Collector Door and Access Panel Gasket:		
PTFE / Fiberglass	Rope, Tadpole Tape	PTFE impregnated for excellent chemical resistance. Service rating to 550° F. Available with wire mesh core to maintain shape under pressure.
High Temperature Fiberglass	Rope, Tape, Bolt Hole Tape, Tadpole Tape	Knitted construction, minimal fraying when cut. No environmental hazards (non-asbestos). Excellent thermal and chemical resistance. Available with pressure sensitive adhesive for ease of application.
Small Diameter Rope:		
Fiberglass	1/8", 3/16", 1/4"	Used as a tie cord or cuff bead
Polyester	3/16"	High density knitted construction. Used as a tie cord or cuff bead